



PELTOR™

Peltor™ WS™ Industrial Adapter

FL6077-WS5, FL6060-WS5

Product description

3M™ Peltor™ WS™ industrial adapter has a built-in Bluetooth® function that allows for complete wireless connection between a 2-way radio and a Peltor WS headset. When used with the Peltor WS Headset XP or the WS ProTac XP, the functions advanced VOX and DSP are available, which gives good sound quality and clear communication.

Article number

FL6077-WS5

FL6060-WS5

Description

WS5 Flex Adapter

WS5 Adapter for Motorola GM350 mobile station

3M ID number

XH001680327

XH001680285



Key Features

- Oil resistant cable
- Digital noise reduction and echo cancellation on incoming audio
- Electronic voice guided menu via the headset

Application

The Peltor™ WS™ industrial adapter can be used with a wide range of Peltor WS headsets to connect to a 2-way radio. For all non-explosive environments.

Accessories

Article number

ACK051

FR05

3M Id number

XH001679642

XH001655469

Description

Rechargeable battery

Charger

Testing and Approval

FL600*-WS5-** is in conformity with the provisions set out in the R&TTE directive 1999/5/EC and the RoHS directive 2011/65/EU. Thereby it fulfils the requirements for CE marking.

The product has been tested and approved in accordance with EN 60950-1:2006 +A1:2010 + A11:2009 + A12:2012, EN300 328 V1.7.1, EN 301 489-1 V1.8.1, EN 301 489-17 V2.1.1

The product has also passed testing according to: FCC 15.247 (Title 47 CFR chapter I part 15 subpart C) FCC 15b (Title 47 CFR chapter I part 15 subpart B), RSS-210 and ICES-103

The product has been examined by

Phoenix Testlab GmbH, Königswinkel 10, D-32825 Blomberg, Germany, Notified body #0700



FL6077-WS5



FL6060-WS5

3M™ Peltor™ Technical Datasheet

Technical Data Specifications

Size: PTT house: 90x70x40 mm

Materials: Box: PP

Cable: Self extinguishing PUR sheeting

Power: The adapter is powered by 2xAA 1.2–1.5V batteries and can use any type, NiMH, NiCd, Alkaline, Lithium, Manganese, etc.



Battery lifetime: Typical battery life time with 2*AA Alkaline batteries is 29 h

Use and storage: Storage temperature: -20°C to +55°C, humidity <90%

Usage temperature: -20°C to +55°C

Maximum recommended shelf life: 5 years except batteries: <1 year

Use limitation: Never modify or alter this product

Model	Cable	Connector	Picture
FL6077-WS5	Oil resistant cable	Flex cable	
FL6060-WS5	Oil resistant cable	10-pole connector	

Flex cable selector

Cable	Description
FL6U-21	Flex Cable for Motorola GP300, CP040
FL6U-28	Flex Cable for Mobile, Dect Phone 2,5 mm Stereo
FL6U-31	Flex Cable for Icom F3, F4, etc 2,5-3,5 mm
FL6U-32	Flex Cable for Motorola GP340, GP328
FL6U-35	Flex Cable for Icom F3G, F4G
FL6U-36	Flex Cable for Kenwood 2,5-3,5 mm
FL6U-61	Flex Cable for Motorola Visar
FL6U-63	Flex Cable for Motorola MOTOTRBO
FL6U-64	Flex Cable for Icom F33/F43 F34/F44
FL6U-65	Flex Cable for Motorola GP344, GP328+
FL6U-66	Flex Cable for Iphone/HTC/Samsung 3,5 mm
FL6U-67	Flex Cable for Nokia/Sony 3,5 mm
FL6U-101	Flex Cable for Sepura STP8000 series
TAA13-T0299	Flex Cable for Icom-F51/61
TAA22-T0299	Flex Cable for Vertex VX-160

Warranty

The warranty does not cover any damage caused by neglected maintenance or careless handling. For more information on maintenance, please see the user instruction.

For full warranty condition, contact your dealer or local 3M office

Important Notice

3M does not accept liability of any kind, be it direct or consequential (including, but not limited to, loss of profits, business and/or goodwill) arising from reliance upon any information herein provided by 3M. The user is responsible for determining the suitability of the products for their intended use. Nothing in this statement will be deemed to exclude or restrict 3M's liability for death or personal injury arising from its negligence.



3M Personal Safety
3M Svenska AB
Box 2341
SE-331 02 Värnamo
Sweden

Phone: +46 (0) 370 65 65 65

Fax: +46 (0) 370 65 65 99

Email: peltorcommunications@mmm.com

Internet: www.3M.com/Peltorcomms

Please recycle. Printed in Sweden.

© 3M 2013. All rights reserved.

Bluetooth is a registered trademark of Bluetooth SIG Inc